# POWER EQUIPMENT

BEPOWEREQUIPMENT

# 3,000 PSI - 3.5 GPM HOT WATER PRESSURE WASHER WITH 7.5HP MOTOR AND GENERAL TRIPLEX PUMP

COMMERCIAL

MODEL: X-HW3075FW3GEN

#### **FEATURES**

- 7.5 HP, three phase premium efficiency, inverterduty motor delivers efficiency and reliability suited for commercial applications.
- **Belt drive system** provides longest pump life possible by lowering its heat, vibration and RPM.
- Commercial grade General triplex pump featuring reinforced body, forged brass manifold, solid ceramic plungers, stainless steel check valves and thermal release valve.
- Auto start/stop system with 8 second time delay. Pump activates only the trigger of the spray wand is squeezed.
- External unloader provides superior cooling and versatility to further enhance pump life.
- Fully insulated, electric powered heater tank. Fully automatic with low water safety shutdown.
- **The heater** can be turned off and controlled with the adjustable thermostat that can be set up to 82°/180°F.
- Industrial grade accessories included are a 50 foot highpressure hose, spray gun wand assembly, and five spray nozzles.



Scan the QR code with your mobile device and discover more about this BE Pressure washer.



### **MOTOR**

MODEL: INVERTER DUTY

 HORSE POWER:
 7.5

 AMPS:
 80

 VOLTS:
 575

 PHASE:
 THREE

AUTO START/STOP: 8 SECOND DELAY

#### **PUMP SPECS**

MODEL: GENERAL TYPE: TRIPLEX

OIL TYPE: **30W NON-DETERGENT**SOAP SYSTEM: **ADJUSTABLE INJECTOR** 

#### **UNLOADER**

TYPE: EXTERNAL W/36" HOSE

#### **HEAT EXCHANGER**

THERMOSTAT: ON/OFF AND ADJUSTABLE

MAX TEMP: 82°C / 180°F

HEATING: **HEATED WATER TANK** 

POWER SOURCE: **ELECTRIC** 

#### **ACCESSORIES**

HOSE TYPE: 50' X 3/8" WIRE BRAIDED

PART NUMBER: **85.238.251** 

NOZZLES: 0°, 15°, 40° AND SOAPER

PART NUMBER: 85.210.035BEP
GUN WAND: 36" INSULATED
PART NUMBER: 85.205.604
FITTINGS: QUICK CONNECT

**FRAME** 

MATERIAL: POWDER COATED

#### **SHIPPING SIZE**

LxWxH: **43" x 20" x 42"**WFIGHT: **695 LBS** 

#### **UNIT SIZE**

LxWxH: **42" x 20" x 41"**WEIGHT: **630 LBS** 

#### **WARRANTY**

MOTOR: 2 YEARS
PUMP: 5 YEARS
HEATER: 3 YEARS
UPC: 777897324921

04-2022

# POWER EQUIPMENT

## LAVEUSE À PRESSION EAU CHAUDE 3,000 PSI - 3.5 GPM **AVEC MOTEUR 7.5 HP &POMPE GENERAL TRIPLEX**

COMMERCIAL

MODÈLE X-HW3075FW3GEN

#### **CARACTÉRISTIQUES**

- Moteur ondulateur trois phases 7.5 HP à efficacité supérieur livrant une fiabilité et efficacité adaptées aux applications commercial.
- Système d'entrainement par courroie prolonge la longévité de la pompe réduisant sa chaleur, vibration et RPM.
- Pompe Général triplex grade commercial avec corps renforcé, collecteur en laiton forgé, pistons en céramique solide, clapets anti-retour en acier inoxydable et soupape de décharge thermique.
- Système marche/arrêt automatique active la pompe quand la gâchette de la lance est pressée.
- Déchargeur externe ournissant en refroidissement et une polyvalence supérieurs afin d'améliorer la durée de vie de la
- Réservoir de chauffage électrique entièrement isolé. Entièrement automatique avec arrêt de sécurité pour manque
- Le bruleur peut être arrêté et contrôlé avec un thermostat ajustable pouvant être configuré jusqu'à 82°/180°F.
- Accessoires grade industriel incluant boyau haute pression 50 pieds, pistolet et lance assemblé, et cinq buses.



**MOTEUR** 

Scannez le code QR avec votre 🚺 cellulaire et apprenez-en plus à propos de cette laveuse 💃 BE Pressure.

### **ÉCHANGEUR DE CHALEUR**

MODÈLE: MOTEUR ONDULEUR PUISSANCE EN CHEVAUX: 7.5

AMPÉRAGE: VOLTS: PHASE: **TROIS** MARCHE/ARRÊT AUTOMATIQUE:

**DÉLAI8 SECONDE** 

SPÉCS POMPE

**GENERAL** MODÈLE: TYPE: **TRIPLEX** TYPE D'HUILE: **30W NON-DÉTERGENT** SYSTÈME DE SAVON: INJECTEUR AJUSTABLE

**DÉCHARGEUR** 

TYPE: **EXTERNE AVEC BOYAU 36"**  THERMOSTAT: MARCHE/ARRÊT AJUSTABLE

MAX CHALEUR: 82°C / 180°F

CHAUFFAGE: **RÉSERVOIR D'EAU CHAUFFÉ** SOURCE D'ALIMENTATION: ÉLECTRIQUE

#### **ACCESSOIRES**

TRESSÉ 50" X 3/8" TYPE DE BOYAU: NUMÉRO PIÈCE: 85.238.251 0°, 15°, 40° ET À SAVON BUSES: NUMÉRO PIÈCE: 85.210.035BEP PISTOLET LANCE: ISOLÉE 36" NUMÉRO PIÈCE: 85.205.604

RACCORDS: **CONNECTION RAPIDE**  **CHÂSSIS** 

MATÉRIEL: CADRE EN ACIER THERMOLAQUÉ

TAILLE D'EXPÉDITION

I xWxH. 43" x 20" x 42" POIDS: 695 LBS

**TAILLE DE LA BOÎTE** 

42" x 20" x 41" LxWxH: POIDS: 630 LBS

**GARANTIE** 

MOTEUR: 2 ANS POMPE: 5 ANS CHAUFFAGE: 3 ANS UPC: 777897324921

04-2022

