B POWER EQUIPMENT

3,500 PSI - 5.5 GPM HOT WATER PRESSURE WASHER WITH HONDA GX690 ENGINE AND GENERAL TRIPLEX PUMP



MODEL · HW3524HG12V

FEATURES

- Powerful Honda GX690 engine with electric start drives the pump. A 55AH Marine battery is included.
- Belt drive system provides longest pump life possible by lowering its heat, vibration and RPM.
- Industrial grade General triplex pump featuring reinforced body, forged brass manifold, solid ceramic plungers, stainless steel check valves and thermal release valve.
- External unloader provides superior cooling and versatility to further enhance pump life.
- Heating coil is ignited by a 12v Beckett burner that is fueled by diesel.
- The burner can be turned off and controlled with the adjustable thermostat that can be set up to 93°/200°F.
- Industrial grade accessories included are a 50 foot highpressure hose, spray gun wand assembly, and five spray nozzles.
- Powder coated steel frame with 1.5" OD roll cage that is designed to mount onto a truck or a trailer.
- Oil drain hoses on the engine and pump allow for easier maintenance with less mess.



Scan the QR code with your mobile device and discover more about this BE Pressure washer.



ENGINE

MODEL: TYPE DISPLACEMENT: FUEL TYPE: FUEL TANK: OIL TYPE:

HONDA GX690 AIR COOLED, 4-STROKE OHV 688CC 86 OCTANE, UP TO 10% ETHANOL 14.4 GALLON **SAE 10W30**

PUMP SPECS

MODEL: TYPE: PART NUMBER: OIL TYPE: SOAP SYSTEM:

UNLOADER

TYPE: PART NUMBER: EXTERNAL W/36" HOSE AL607

30W NON-DETERGENT

ADJUSTABLE INJECTOR

GENERAL TSF2021

TRIPLEX

85.130.026B

BURNER

THERMOSTAT MAX HEAT: IGNITER: HEATING COIL: FUEL CAPACITY: FUEL TYPE:

ACCESSORIES

HOSE TYPE PART NUMBER: NOZZLES: PART NUMBER: GUN WAND: PART NUMBER: FITTINGS:

ON/OFF AND ADJUSTABLE 93°C / 200°F **12V BECKETT BURNER** 1/2" COLD ROLLED STEEL COIL TUBE LENGTH: 96' LENGTH OF TUBING 14.4 GALLON DIESEL

> 50' X 3/8" WIRE BRAIDED 85.238.251 0°, 15°, 25°, 40° AND SOAPER 85.210.060H **47" INSULATED** 85.205.066H QUICK CONNECT

MATERIAL:

FRAME

POWDER COATED

SHIPPING SIZE

LxWxH: 48" x 46" x 51" WEIGHT: 975 LBS

UNIT SIZE LxWxH: WEIGHT:

46" x 44" x 48" 930LBS

WARRANTY

ENGINE: **3 YEARS** PUMP: 5 YEARS HEATING COIL: 3 YEARS UPC: 777897309010

04-2022



THE POWER YOU NEED.

BE POWER EQUIPMENT

3,500 PSI - 5.6 GPM HOT WATER PRESSURE WASHER WITH HONDA GX690 ENGINE AND GENERAL TRIPLEX PUMP



MODEL: HW3524HG12V

FEATURES

- Powerful Honda GX690 engine with electric start drives the pump. A 55AH Marine battery is included.
- Belt drive system provides longest pump life possible by lowering its heat, vibration and RPM.
- Industrial grade General triplex pump featuring reinforced body, forged brass manifold, solid ceramic plungers, stainless steel check valves and thermal release valve.
- External unloader provides superior cooling and versatility to further enhance pump life.
- Heating coil is ignited by a 12v Beckett burner that is fueled by diesel.
- The burner can be turned off and controlled with the adjustable thermostat that can be set up to 93°/200°F.
- Industrial grade accessories included are a 50 foot highpressure hose, spray gun wand assembly, and five spray nozzles.
- Powder coated steel frame with 1.5" OD roll cage that is designed to mount onto a truck or a trailer.
- **Oil drain hoses** on the engine and pump allow for easier maintenance with less mess.



Scan the QR code with your mobile device and discover more about this BE Pressure washer.



ENGINE

MODEL: TYPE: DISPLACEMENT: FUEL TYPE: FUEL TANK: OIL TYPE:

HONDA GX690 AIR COOLED, 4-STROKE OHV 688CC **86 OCTANE, UP TO 10% ETHANOL** 14.4 GALLON **SAE 10W30**

PUMP SPECS

MODEL:	GENERAL TSF2021
TYPE:	TRIPLEX
PART NUMBER:	85.130.026B
OIL TYPE:	30W NON-DETERGENT
SOAP SYSTEM:	ADJUSTABLE INJECTOR

UNLOADER

TYPE: PART NUMBER: EXTERNAL W/36" HOSE AL607

BURNER

THERMOSTAT: MAX HEAT: IGNITER: HEATING COIL: FUEL CAPACITY: FUEL TYPE:

ACCESSORIES

HOSE TYPE: PART NUMBER: NOZZLES: PART NUMBER: GUN WAND: PART NUMBER: FITTINGS:

ON/OFF AND ADJUSTABLE 93°C / 200°F **12V BECKETT BURNER** 1/2" COLD ROLLED STEEL COIL TUBE LENGTH: 96' LENGTH OF TUBING 14.4 GALLON DIESEL

> 50' X 3/8" WIRE BRAIDED 85.238.251 0°, 15°, 25°, 40° AND SOAPER 85.210.060H 47" INSULATED 85.205.066H QUICK CONNECT

FRAME MATERIAL:

POWDER COATED

SHIPPING SIZE

LxWxH:	48" x 46" x 51"
WEIGHT:	975 LBS

UNIT SIZE	
LxWxH:	46" x 44" x 48"
WEIGHT:	930LBS

WARRANTY

ENGINE:	3 YEARS
PUMP:	5 YEARS
BURNER:	3 YEARS
UPC:	777897309010

THE POWER YOU NEED.

